

TOOLS NEEDED:

- Phillips screwdriver
- Flat head screwdriver
- 10mm Socket



INSTALLATION DIFFICULTY:

TIME OF INSTALLATION:

Approximately
15 Minutes

We highly recommend that you check your filter every 3000 miles or sooner in harsh environments. For complete cleaning instructions please see the enclosed Green booklet.

For complete filter warranty information please refer to the enclosed Green booklet.

If you live or travel in a harsh environment we recommend that you purchase a Quadzilla Pre-Filter.

Quadzilla Pre-Filters are designed for the purpose of preventing large particles such as rubbery, dirt and sand from clogging the filter pleats. Premature clogging of an air filter will result in loss of horsepower and an increase in service intervals. Quadzilla pre-filters are uniquely designed to protect your engine and the performance air filter investment without sacrificing airflow or horsepower.

THIS IS A HIGH PERFORMANCE PRODUCT. USE AT YOUR OWN RISK

Do not use this product until you have carefully read the following agreement.

This sets forth the terms and conditions for the use of this product. The installation of this product indicates the BUYER has read and understands this agreement and accepts the terms and conditions.

DISCLAIMER OF LIABILITY

Quadzilla Performance Technologies, Inc. and its distributors, jobbers and dealers (hereafter SELLER) shall in no way be responsible for the products proper use and service. THE BUYER HERBY WAVES ALL LIABILITY CLAIMS.

The BUYER acknowledges that he/she is not relying on the SELLER's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof and the BUYER hereby waives all remedies or liabilities, expressed or implied arising by law or otherwise, (including without any obligations of the SELLER with respect to fitness, merchantability and consequential damages) or whether or not occasioned by the SELLER's negligence.

The SELLER disclaims any warranty and expressly disclaims any liability for personal injury or damages. The BUYER acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the BUYER agrees to indemnify the SELLER and to hold the SELLER harmless from any claim related to the item of the equipment purchased. Under no circumstances will the SELLER be liable for any damages or expenses by reason of use or sales of such equipment.

The SELLER assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt, contact the manufacturer.

LIMITATION OF WARRANTY

Quadzilla Performance Technologies, Inc. (hereafter "SELLER") gives limited warranty as to description, quality, merchantability, fitness for any product's purpose, productiveness, or any other matter of SELLER's product herewith. The SELLER shall be in no way responsible for the product's open use and service and the BUYER hereby waives, all rights other than those expressly written herein. This warranty shall not be extended or varied in except by a written instrument signed by SELLER and BUYER.

The warranty is limited to one (1) year from the date of sale and limited solely to the parts contained within the product's kit. All products that are in question of Warranty must be returned shipping prepaid to the SELLER and must be accompanied by a dated proof of purchase receipt. All warranty claims are subject to approval by Quadzilla Performance Technologies, Inc

Under no circumstances shall the SELLER be liable for any labor charged or travel time incurred in diagnosis for defects, removal, or reinstallation of this product, or any other contingent expenses.

Under no circumstances shall the SELLER be liable for any damages or expenses insured by reason of the use of sale of any such equipment.

THE INSTALLATION OF THIS PRODUCT INDICATES THAT THE BUYER HAS READ AND UNDERSTANDS THIS AGREEMENT AND ACCEPTS ITS TERMS AND CONDITIONS.

QUADZILLA PERFORMANCE

MAIC



GM 6.6 Liter Instruction Manual



WWW.QUADZILLAPOWER.COM

WWW.QUADZILLAPOWER.COM

Instructions



01-05 Duramax Intake

1 Removing Stock Air Filter

1A Remove the factory mass air sensor using a Phillips head screwdriver.

1B Loosen the band clamp holding the rubber intake tube to the air box using a flat head screwdriver or a 5/16 nut driver.

1C Remove the factor air box by gently lifting it straight out of the vehicle.



2 Installing the Quadzilla Monster Air Intake

2A Remove the filter from the Monster Air Intake. Be careful not to damage the filter pleats when handling the filter.




2B Remove the four bolts holding the intake tray onto your vehicle using a 10mm socket. The plate will stay in place and the new intake will sit on top of it.

2C Install the Quadzilla Monster Air Intake by aligning the holes in the intake with the holes where bolts were removed. Attach the intake to the truck by fastening the factory bolts into the 4 holes and tightening them.



2D Install the filter back on the intake.

2E Reinstall the factory mass air sensor into the Quadzilla Monster Air Intake using the two supplied Phillips head machine screws. Re-attach the rubber intake tube to the Quadzilla Monster Air Intake and tighten the band clamp.



Notes:

We recommend that you store any stock pieces that have been removed. If for any reason you decide to reinstall the stock intake you will need all of these pieces.

www.QuadZillaPower.com