

Notice to Customer: Please fax the following information to BD Diesel Performance to complete this installation. Fax # 1-604-853-6089

BD Invoice # (if known):				
			Custome	er Information
Company:				Contact :
Address:				Zip/Postal Code:
Phone #				Fax #:
Email:				
Vehicle Information				
Vin #:				
Mileage at installation:				
Transmission Serial Number :				
Installer Information				
Company:				Contact:
Name:				Date of Install:
Verification of pressures				
Pressure at Idle (In Drive): (Should be 60-70 PSI)				
Pressure at wide open throttle (In Drive):				(Should be 230-260 PSI with a mechanical gauge)
** Wide open throttle pressures MUST be taken while the transmission is in lock up AFTER DRIVE LEARN				
				(300 PSI Manual Gauge)**
		68RF	E Clutch Flu	uid Index Data Sheet
Readings Must be done with a 300 PSI Manual Gauge with the				
		S	upplie	d adapter.
	INITIAL	AFTER QUIC	k Learn	DRIVE LEARN AFTER VALUE'S STABILIZE (50-100 KMS)
LR				
2-4 OR 2C				
UD				
OD				
4C				
Norm N-1 UD				
Alternate 4C				
1 st 2-3 OD				
Alternate 2C 1 st N-1 UD				
I N-I UD	INITIAL	AFTER QUIC		DRIVE LEARN AFTER VALUE'S STABILIZE (50-100 KMS)
2-4 Shift	INITIAL	AFTER QUIC		DRIVE LEARN AFTER VALUE 3 STABILIZE (30-100 RWS)
2-4 Shint 2C				
1st N-UD				
1st 3-4 OD				
LR				
LR				
Alt 2C				
4C				
UD				
UD				
Norm N-D UD				
OD				
OD				
Please fill out applicable section as information differs dependent on model year.				